

■ ■ ■
■ ■ ■

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Certificate of conformity of the factory production control 0432-CPR-00215-15 (EN)

Version 02

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Single wall chimney system and flue pipes made of stainless steel 1.4404 (AISI 316L) for wet applications

(for a detailed product description see annex 1 of this certificate)

placed on the market under the name or trade mark of

Cox Geelen B.V.

Emmastraat 92
NL-6245 HZ Eijsden, Netherlands

and produced in the manufacturing plant(s)

Cox Geelen B.V.

Emmastraat 92
NL-6245 HZ Eijsden, Netherlands

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1856-1:2009

under **system 2+** are applied and that

the factory production control is assessed to be in conformity with the applicable requirements

This certificate was first issued on 24.05.2016 and will remain valid until 19.04.2026 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 20.04.2021

by order


Dipl.-Ing. Hönig

deputy Head of Certification Body (Dept. 21)



This Certificate consists of 1 page and 1 annex(es).

This Certificate replaces the Certificate no. 0432-CPR-00215-15
dated 24.05.2016, Version 01.

The original of this document was issued in German language.
In case of doubt only the German version is valid.



Vom Hersteller erklärte Eigenschaften für / Declared conditions by the manufacturer for:

| | Art der Abgasanlage/ Leitung <i>type of chimney/ flue pipe</i> | Harmonisierte Norm <i>standard</i> | Produktbeschreibung <i>Product description</i> |
|----|--|--|--|
| 01 | einschaliger Systemschornstein und Abgasleitungen für feuchte Anwendungen <i>single wall system chimney and flue pipes for wet applications</i> für Überdruck P1 / <i>for excess pressure P1</i> für Gas und Öl / <i>for gas and oil</i> Rohr / <i>pipe</i> : 1.4404 (AISI 316L) Wanddicke / <i>wall thickness</i> : 0,40 mm | EN 1856-1 | T200 – P1 – W – Vm – L50040 – O(50) DN 80 – DN 130 Abstand zu brennbaren Bauteilen: <i>distance to combustibles</i> : O: 50 mm |

2. Ausfertigung / *second copy*