

Notified Body
Nr. 0036



Industrie Service

Certificate of conformity of the factory production control

0036 CPR 9184 001

Revision 07

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

System chimney, flue liner of rigid and flexible pipes and fittings of PP models

without outer liner, rigid	EN 14471	T120 H1 W 2 O20 XXX
with plastic outer liner, rigid	EN 14471	T120 H1 W2 O00 LI E U1
with metal outer liner, rigid	EN 14471	T120 H1 W2 O00 LE E U0
with mineral shaft, flexible	EN 14471	T120 H1 W2 O00 LE E U0

for details of classification see page 2

produced by

**Skoberne GmbH
Ostendstraße 1
64319 Pfungstadt**

in the manufacturing plant

Werk 1	Werk 2	Werk 3	Werk 4	Werk 5
---------------	---------------	---------------	---------------	---------------

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14471:2013+A1:2015

under system 2+ are applied and that the factory production control fulfils all the prescribed requirements set out above.

The determination of the product type on the basis of type testing is documented in the following report: TÜV SÜD Industrie Service GmbH no. A 1614-00/06, A 1614-02/09, A 1614-03/09, A 1614-04/09, A 1614-05/10, A 1614-06/10, A 1614-07/10, A 1614-09/12 and A 1614-14/16.

This certificate was first issued on 2007-02-27 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Munich, 2016-06-10

Johannes Steiglechner
Leiter Zertifizierungsstelle Bauprodukte (EG)



System chimney with flue liner of rigid and flexible pipes and fittings of PP	EN 14471
without outer liner	
DN 80 - DN 110, black	T120 H1 W2 O20 LE E U
DN 60 - DN 250, white, grey	T120 H1 W2 O20 LI E U
with plastic outer liner, rigid ≤ DN 80, white	T120 H1 W2 O00 LI E U1
with metal outer liner, rigid ≤ DN 250, white, grey, black,	T120 H1 W2 O00 LE E U0
with mineral shaft, flexible DN 60 – DN 110	T120 H1 W2 O00 LE E U0