

Materialprüfungsamt Nordrhein-Westfalen

Prüfen • Überwachen • Zertifizieren

**Certificate of conformity of the factory production control
0432-CPR-00215-30 (EN)**

Version 03

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

concentric air-flue-system

made of aluminium alloy: EN AW-6060 and EN AW-4047A

"CoxCentric"®*(for a detailed product description see annex 1 of this certificate)*

placed on the market under the name or trade mark of

Cox Geelen B.V.Emmastraat 92
6245 HZ Eijsden / Netherlands

and produced in the manufacturing plant(s)

Cox Geelen B.V.Emmastraat 92
NL-6245 HZ Eijsden / Netherlands


This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1856-1:2009under **system 2+** are applied and that**the factory production control is assessed to be in conformity
with the applicable requirements**

This certificate was first issued on 01.04.2015 and will remain valid until 27.03.2030 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 28.03.2025

by order


Dipl.-Ing. Becker
Certification Body (Dep. 21.30)

This Certificate consists of 1 page and 1 annex(es).

This Certificate replaces the Certificate no. 0432-CPR-00215-30
dated 16.03.2020, Version 02.*The original of this document was issued in German language.
In case of doubt only the German version is valid.*

Vom Hersteller erklärte Eigenschaften für / Declared conditions by the manufacturer for:

	Art der Abgasanlage/ Leitung <i>type of chimney/ flue pipe</i>	Harmonisierte Norm <i>standard</i>	Produktbeschreibung <i>Product description</i>
01	"CoxCentric ®" Konzentrisches Luft-Abgas-System/ <i>Concentric air-flue-system</i> Innenrohr / inner pipe: EN AW-6060 Innenbogen / innen bow: EN AW-4047A Wanddicke / wall thickness: 1,5 mm, (-10 %) Außenrohr / outer pipe: EN AW-1200A Wanddicke / wall thickness: 0,4 mm, (-10 %)	EN 1856-1:2009	T200 – H1 – W – Vm – L10/13150 – 0(00) DN 60/100, DN 80/125, DN 100/150 Abstand zu brennbaren Bauteilen: <i>distance to combustibles:</i> 0: 0 mm