

Notified Body
Nr. 0036



Industrie Service

Certificate of conformity of the factory production control

0036 CPR 91367 001
Revision 03

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

System chimney with inner liner of rigid / flexible pipes and fittings of PP

	models	
System 0.1	EN 14471	T120 H1 W2 O20 LE E U
System 0.2	EN 14471	T120 H1 W2 O00 LE E U0
System 0.3	EN 14471	T120 H1 W2 O00 LE E U0
System 0.4	EN 14471	T120 H1 W2 O00 LE E U1
System 0.5	EN 14471	T120 H1 W2 O00 LE E U0
System 0.6	EN 14471	T120 H1 W2 O00 LE E U0

for details of classification see page 2

produced by

CoxGeelen BV
Emmastraat 92
NL-6245 HZ Eijsden (L)

in the manufacturing plant

Emmastraat 92
NL-6245 HZ Eijsden (L)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14471:2013 +A1:2015

under system 2+ are applied and that the factory production control fulfils all the prescribed requirements set out above.

The determination of the product type on the basis of type testing is documented in the following report: TÜV SÜD Industrie Service GmbH no. A 2037-00/13, A 2037-01/15, A 2037-02/16, A 2037-03/16, A 2037-04/16, A 2037-05/16, A 2037-06/16, A 2037-07/16 and A 2037-10/17.

This certificate was first issued on 2013-10-31 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Munich, 2017-10-04

Johannes Steiglechner
Leiter Zertifizierungsstelle Bauprodukte (EG)



System chimney with rigid/flexible PP liner	EN 14471:2013 + 2015:A1
rigid, without outer liner System 0.1	T120 H1 W2 O20 LE E U
rigid, with outer liner of metal System 0.2	T120 H1 W2 O00 LE E U0
System 0.3	T120 H1 W2 O00 LE E U0
rigid, with outer liner of PP System 0.4	T120 H1 W2 O00 LE E U1
rigid, for installation in noncombustible outer shaft System 0.5	T120 H1 W2 O00 LE E U0
flexible, with specified outer liner System 0.6	T120 H1 W2 O00 LE E U0