

Materialprüfungsamt Nordrhein-Westfalen

Prüfen • Überwachen • Zertifizieren

**Certificate of conformity of the factory production control
0432-CPR-00215-10 (EN)**

Version 02

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

single wall chimney system

made of aluminum alloy: EN AW-6060, EN AW-1200A and EN AW-4047A

„CoxFix®“

(for a detailed product description see annex 1 of this certificate)

placed on the market under the name or trade mark of

Cox Geelen B.V.Emmastraat 92
6245 HZ Eijsden, Netherlands

and produced in the manufacturing plant(s)

Cox Geelen B.V.Emmastraat 92
6245 HZ Eijsden, Netherlands

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1856-1:2009under **system 2+** are applied and that**the factory production control is assessed to be in conformity
with the applicable requirements**

This certificate was first issued on 01.04.2015 and will remain valid until 31.03.2025 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.



Dortmund, 16.03.2020

by order


Dipl.-Ing. Hönig
Head of Certification Body (Dept. 21)

This Certificate consists of 1 page and 1 annex(es).

This Certificate replaces the Certificate no. 0432-CPR-00215-10
dated 18.06.2015, Version 01.The original of this document was issued in German language.
In case of doubt only the German version is valid.

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Vom Hersteller erklärte Eigenschaften für / *Declared conditions by the manufacturer for:*

	Art der Abgasanlage/ Leitung <i>type of chimney / flue pipe</i>	Harmonisierte Norm <i>standard</i>	Produktbeschreibung <i>Product description</i>
01	„CoxFix®“ Einwandige Abgasanlage/ <i>single wall chimney system</i> Rohr / <i>pipe</i> : ≤ DN 100: EN AW-6060 DN 110 – DN 130: EN AW-1200A Bogen/ <i>bow</i> : EN AW-4047A Wanddicke / <i>wall thickness</i> : 1,5 mm, (-10 %)	EN 1856-1:2009	T200 – H1 – W – Vm – L10/13150 – O(50) ≤ DN 100 T200 – P1 – W – Vm – L10/11150 – O(50) DN 110 – 130 Abstand zu brennbaren Bauteilen: <i>distance to combustibles</i> : O: 50 mm

2. Ausfertigung / *second copy*